

# Auracast

	<b>AuraLoop</b>	Tragbare Hybridstation mit integrierter Loop- und Auracast-Technologie für Tischgeräte. Konfigurierbar mit der AuraConnect-App.	<u>C3</u>	525.–
	<b>AuraLoop+</b>	Tragbare Hybridstation mit integrierter Schleifen- und Auracast-Technologie für Tischgeräte. Konfigurierbar mit der AuraConnect-App. Im Lieferumfang enthalten sind ein Mikrofon und ein Ohrhörer für Personen ohne Hörgeräte.	<u>C3</u>	665.–
	<b>Aura-CA</b>	Mini-Auracast-Sender für Empfangsgeräte, Reichweite 15 m. Lieferung mit Netzteil in Kunststoffgehäuse. Konfigurierbar mit der AuraConnect-App.	<u>C3</u>	300.–
	<b>Aura-CA1</b>	Mini-Auracast-Sender für Empfangsgeräte, geliefert mit einem OP-M81-Schwannenhals-Fernmikrofon, Reichweite 15 m. Lieferung mit Netzteil in Kunststoffkoffer und Montagezubehör. Konfigurierbar mit der AuraConnect-App.	<u>C3</u>	370.–
	<b>AuraGateLite</b>	Weißer Auracast-Sender für Geräte in kleinen Räumen. Reichweite von 30 m im Freifeld. Kommt mit Netzteil.	<u>C3</u>	1'130.–
	<b>AuraGate-WH</b>	Auracast-Sendeempfänger in Weiß für Raumausstattung. Reichweite im Freifeld 100 m. Lieferung inklusive Netzteil.	<u>C3</u>	1'775.–
	<b>AuraGate-BL</b>	Dito, schwarz	<u>C3</u>	1'775.–
	<b>AuraGate-NETWH</b>	Weisser Auracast Sender mit Dante und Netzwerksteuerung über POE+. 100 m Reichweite im Freifeld. Lieferung inklusive Netzteil.	<u>C3</u>	2'440.–
	<b>AuraGate-NETBL</b>	Dito, schwarz	<u>C3</u>	2'440.–
	<b>AuraSTRX BK</b>	Universeller Auracast-Transceiver mit Touchscreen zum Empfangen und Senden von Auracast-Streams. Integriertes Mikrofon, QR-Code-Lesegerät, Beschleunigungsmesser, USB-C- und 3,5-mm-Klinkenstecker.	<u>C3</u>	410.–
	<b>AurOEM</b>	Auracast-Industrieadapterkarte zur Ausstattung aktiver Produkte mit Lautsprechern, wie z. B. digitale Kiosksysteme, Werbekiosksysteme, Gegensprechanlagen usw. Konfigurierbar mit der AuraConnect-App.	<u>C3</u>	190.–

## Zubehör

	TR-iL	Magnetische Halsspule für AuraSTRX	<u>C3</u>	65.-
	OP-778	Headset für AuraSTRX	<u>C3</u>	35.-
	M-801S	Headband electret microphone	<u>C3</u>	130.-
	W-68T	Clip-on microphone	<u>C3</u>	60.-
	Aura-CH5	5-fach-Ladeschale für AuraSTRX, USB	<u>C3</u>	655.-
	Aura-CH10	10-fach-Ladeschale für AuraSTRX, USB	<u>C3</u>	835.-
	Aura-CHRACK	Rackmount für AURA-CH10	<u>C3</u>	60.-
	AURA-FXMIC	AuraGate mounting bracket für Mikrofonschale	<u>C3</u>	70.-
	AuraConnect	 		

# Induction Loop

## Amplifiers

	<b>eLoop</b>	Portable loop amplifier with 5V power supply, lithium battery, mounting bracket and information sticker	<u>C3</u>	285.-
	<b>eLoop+</b>	Portable loop amplifier with handset, OP-M80 gooseneck microphone, 5V power supply, lithium battery, mounting bracket and information sticker	<u>C3</u>	345.-
	<b>HDC20</b>	HDC20 is an 3.5Arms loop system for reception counter with possibility to connect an Opus Auracast broadcaster (Aura-CA). Supplied with a 24V 3A power supply.	<u>C3</u>	250.-
	<b>HDC20-K</b>	Complete kit. Including a HDC20 loop amplifier, a copper cable with its connections, an external power supply, a surface microphone and a "area adapted for hearing-impaired " sticker.	<u>C3</u>	275.-
	<b>HDC20-K1</b>	Complete kit. Including a HDC20 loop amplifier, a copper cable with its connections, an external power supply, a gooseneck microphone and an "area adapted for hearing-impaired " sticker.	<u>C3</u>	335.-
	<b>HDC20-K2</b>	Complete kit. Including a HDC20 loop amplifier, a copper cable with its connections, an external power supply, a gooseneck microphone, a handset OP-E3 and an "area adapted for hearing-impaired " sticker.	<u>C3</u>	375.-
	<b>HDC20-Wall</b>	Complete kit. Including a HDC20 loop amplifier, a loop pictogram OP-WALL2 to fix, an external power supply, a surface-mount microphone and a « adapted for hearing-impaired area » sticker.	<u>C3</u>	380.-
	<b>HMD1.0A</b>	The HMD1.0 is a hybrid solution integrating a 3.5A loop amplifier and an Auracast transmitter for rooms up to 100m <sup>2</sup> with its standard 24V 3A power supply, 150m <sup>2</sup> with the PS-HMD32V power supply .	<u>C3</u>	895.-
	<b>HMD1.0A-SA</b>	The HMD1.0-SA kit is a 3.5Arms loop amplifier with possibility to connect an Opus Auracast broadcaster for rooms up to 100m <sup>2</sup> with its standard 24V 3A power supply, 150m <sup>2</sup> with the PS-HMD32V power supply (option). The kit is supply with HMD1.0, a 30 meters wire cable, a surface-mount microphone and an "area adapted for hearing-impaired " sticker.	<u>C3</u>	940.-
	<b>HMD1.0A-TV</b>	The HMD1.0-SA kit is a 3.5Arms loop amplifier with possibility to connect an Opus Auracast broadcaster for rooms up to 100m <sup>2</sup> with its standard 24V 3A power supply, 150m <sup>2</sup> with the PS-HMD32V power supply (option) . The kit is supply with HMD1.0, a 30 meters wire cable, a digital-analog converte, a surface-mount microphone and an "area adapted for hearing-impaired " sticker.	<u>C3</u>	940.-
	<b>HMD1.2A</b>	The HMD1.2 is a 2 channels loop amplifier (2x3.5Arms) with possibility to connect an Opus Auracast broadcaster for rooms up to 100m <sup>2</sup> with its standard 24V 3A power supply, 150m <sup>2</sup> with the PS-HMD32V power supply (option).	<u>C3</u>	1'155.-
	<b>PS-HMD32V</b>	Power supply of 32V 3A to extend HMD's coverage up to 150m <sup>2</sup> . With this power supply the HMD series supply 4,2Arms of current output.	<u>C3</u>	60.-

	<b>DCL20</b>	Induction loop amplifier for counters and small room, provided with its power supply and two stickers "adapted for hearing-impaired area"	<u>C3</u>	230.-
	<b>DCL20-K</b>	Complete kit. Including a DCL20 induction loop amplifier, a copper cable with its connections, an external power supply, a surface microphone and a "area adapted for hearing-impaired " sticker	<u>C3</u>	260.-
	<b>DCL20-K1</b>	Complete kit. It includes a DCL20 induction loop amplifier, a copper cable and its connections, and external power supply, a gooseneck microphone and an "area adapted for hearing-impaired " sticker	<u>C3</u>	325.-
	<b>DCL20-K2</b>	Complete kit. It includes a DCL20 amplifier, a copper cable with its connections, an external power supply, a gooseneck microphone, a telephone handset OP-E2 and an "area adapted for hearing-impaired " sticker.	<u>C3</u>	370.-
	<b>DCL20-E3</b>	Complete kit. It includes a DCL20 amplifier, a copper cable with its connections, an external power supply, a surface-mount microphone, a telephone handset OP-E3 and an "area adapted for hearing-impaired " sticker.	<u>C3</u>	310.-
	<b>DCL20-WALL</b>	Complete kit. It includes a DCL20 amplifier, a loop pictogram OP-WALL2 to fix, an external power supply, a surface-mount microphone and a « adapted for hearing-impaired area » sticker	<u>C3</u>	375.-
	<b>DCL20-PLUG</b>	Complete kit. It includes a DCL20 amplifier, a loop pictogram OP-WALL2 with its easel OP-CHW2, an external power supply, a surface-mount microphone and a « adapted for hearing-impaired area » sticker.	<u>C3</u>	400.-
	<b>DCL20-SA</b>	Kit for small room. It includes a DCL20 induction loop amplifier, a 30 meters wire cable, an external power supply, a surface-mount microphone and an "area adapted for hearing-impaired " sticker	<u>C3</u>	315.-
	<b>DCL20-TV</b>	Kit for TV room. It includes a DCL20 induction loop amplifier, a 30 meters wire cable, a digital-analog converter, an external power supply, a surface-mount microphone and an "area adapted for hearing-impaired " sticker	<u>C3</u>	355.-

# Induction Loop

## LD SERIES Amplifiers

	<b>LD1.0Lite</b>	Rackable 4A loop amplifier for up to 180 m <sup>2</sup> room. Mounting kit for racking not supplied	<u>C3</u>	605.-
	<b>LD1.0</b>	Rackable 5A loop amplifier for up to 250 m <sup>2</sup> room. Mounting kit for racking not supplied	<u>C3</u>	820.-
	<b>LD1.2</b>	2x5A loop amplifier for low-spill systems or very wide coverage (≈600m <sup>2</sup> ). Rack mounting kit supplied	<u>C3</u>	1'550.-
	<b>LD2.0</b>	Rackable 7A loop amplifier for up to 450 m <sup>2</sup> room. Rack mounting kit not supplied	<u>C3</u>	940.-
	<b>LD2.2</b>	2x7A induction loop amplifier for low-spill systems or very wide coverage (≈1200m <sup>2</sup> ). Rack mounting kit supplied	<u>C3</u>	1'865.-
	<b>LD3.0</b>	Rackable 10A loop amplifier for up to 1000 m <sup>2</sup> . Rack mounting kit not supplied	<u>C3</u>	1'055.-
	<b>LD3.2</b>	2x10A induction loop amplifier for low-spill systems or very wide coverage (≈2000m <sup>2</sup> ). Rack mounting kit supplied.	<u>C3</u>	2'185.-
	<b>LD4.2</b>	2x15A LD3.0 induction loop amplifier for low-spill systems or very wide coverage (≈3300m <sup>2</sup> ). Rack mounting kit supplied	<u>C3</u>	2'630.-

# Induction Loop

## LDP Mobile loop system

	<b>LDP1.0</b>	Mobile loop system integrated in a suitcase including: 1 LD1.0 amplifier, a storage locker, an OP-FSM-02 and a 100 meters cable pool	<u>C3</u>	1'875.-
	<b>LDP2.0</b>	Mobile loop system integrated in a suitcase including: 1 LD2.0 amplifier, a storage locker, an OP-FSM-02 and a 100 meters cable pool	<u>C3</u>	1'980.-
	<b>LDP3.0</b>	Mobile loop system integrated in a suitcase including: 1 LD3.0 amplifier, a storage locker, an OP-FSM-02 a 100 meters cable pool	<u>C3</u>	2'290.-
	<b>LDP1.0M</b>	Mobile loop system integrated in a suitcase including: 1 LD1.0 amplifier, a wireless microphone OPUS 10, a storage locker, an OP-FSM-02 field mesurer and a 100 meters cable pool	<u>C3</u>	2'515.-
	<b>LDP2.0M</b>	Mobile loop system integrated in a suitcase including: 1 LD2.0 amplifier, a wireless microphone OPUS 10, a storage locker, an OP-FSM-02 field mesurer and a 100 meters cable pool	<u>C3</u>	2'640.-
	<b>LDP3.0M</b>	Mobile loop system integrated in a suitcase including: 1 LD3.0 amplifier, a wireless microphone OPUS 10, a storage locker, a OP-FSM-02 and a 100 meters cable pool	<u>C3</u>	2'770.-

# Induction Loop Zubehör

	<b>LC-50</b>	Cable with a variable resistance from 0.5mm <sup>2</sup> to 2.5mm <sup>2</sup> for induction loop. It can be installed through a floor, a wall, or a ceiling. 50 meters spool	<u>C3</u>	180.-
	<b>LC-100</b>	Cable with a variable resistance from 0.5mm <sup>2</sup> to 2.5mm <sup>2</sup> for induction loop. It can be installed through a floor, a wall, or ceiling. 100 meters-coil	<u>C3</u>	335.-
	<b>LC-150</b>	Cable with a variable resistance from 0.5mm <sup>2</sup> to 2.5mm <sup>2</sup> for induction loop. It can be installed through a floor, a wall, or a ceiling. 150 meters spool.	<u>C3</u>	490.-
	<b>DBLC15-100</b>	Direct burrial loop cable, 1,5mm- 100m reel	<u>C3</u>	510.-
	<b>DBCL25-200</b>	Direct burrial loop cable, 2,5mm- 100m reel 200m drum	<u>C3</u>	1005.-
	<b>RC50</b>	19 mm Isolated flat copper tape for ground installation. 50 meters spool	<u>C3</u>	165.-
	<b>RC100</b>	19 mm Isolated flat copper tape for ground installation. 100 meters spool	<u>C3</u>	315.-
	<b>RC150</b>	19 mm Isolated flat copper tape for ground installation. 150 meters spool	<u>C3</u>	460.-

	<b>RC01-50</b>	10 mm Isolated flat copper tape for ground installation. 50 meters spool	<u>C3</u>	130.-
	<b>RC01-100</b>	10 mm Isolated flat copper tape for ground installation. 100 meters spool	<u>C3</u>	245.-
	<b>RC02-50</b>	2x10 mm Isolated flat copper tape for ground installation. 50 meters spool.	<u>C3</u>	200.-
	<b>RC02-100</b>	2x10 mm Isolated flat copper tape for ground installation. 100 meters spool.	<u>C3</u>	395.-
	<b>RC025-100</b>	25 mm Isolated flat copper tape for ground installation. 100 meters spool	<u>C3</u>	475.-
	<b>RC025-200</b>	25 mm Isolated flat copper tape for ground installation. 200 meters spool	<u>C3</u>	530.-
	<b>OP-LI5</b>	Copper shielded link cable which allows to connect an induction loop to an amplifier. Length: 5 meters	<u>C3</u>	55.-
	<b>OP-LI10</b>	Copper shielded link cable which allows to connect an induction loop to an amplifier. Length: 10 meters.	<u>C3</u>	80.-
	<b>OP-LI15</b>	Copper shielded link cable which allows to connect an induction loop to an amplifier. Length: 15 meters	<u>C3</u>	95.-
	<b>C10-RC</b>	Terminal block to connect an OP-LI cable to a flat copper tape RC. 10 units	<u>C3</u>	60.-

	<b>ADH-RC</b>	Protective warning adhesive tape "do not cut", for flat copper tape RC50-100-150	<u>C3</u>	30.-
	<b>OP-LR</b>	Loop receiver/mesurer with chargeable battery	<u>C3</u>	160.-
	<b>OP-LRM</b>	Loop receiver / mesurer with headset and chargeable battery	<u>C3</u>	185.-
	<b>OP-FSM</b>	Magnetic field mesurer to set a loop system in accordance with the EN601118-4 standard	<u>C3</u>	285.-
	<b>OP-FSM-02</b>	Magnetic field mesurer to set a loop system in accordance with the EN601118-4 standard. Supplied with headphones	<u>C3</u>	295.-

# Window Intercom System

	<b>STI-01</b>	Touchpad counter intercom with headphone jack	<u>C3</u>	370.-
	<b>STI-01B</b>	Touchpad counter intercom with magnetic loop	<u>C3</u>	555.-
	<b>STI-01H</b>	Touchpad counter intercom with headphone jack	<u>C3</u>	475.-
	<b>STI-01HB</b>	Touchpad counter intercom with micro-headphone jack and magnetic loop	<u>C3</u>	660.-
	<b>OP-6510</b>	Digital counter intercom with press buttons	<u>C3</u>	645.-
	<b>OP-6510B</b>	Digital counter intercom with press buttons, loop cable and magnetic loop amplifier. Suitable for hearing impaired people	<u>C3</u>	865.-
	<b>OP-6505H</b>	Digital counter intercom with touch-sensitive pad. English message.	<u>C3</u>	900.-
	<b>OP-6505HB</b>	Digital counter intercom with touch-sensitive pad, loop cable and magnetic loop amplifier, suitable for hearing impaired people	<u>C3</u>	1'125.-
	<b>OP-6505HK</b>	Digital counter intercom with touch-sensitive pad, and headset mic HD-1022	<u>C3</u>	1'010.-
	<b>OP-6505HBK</b>	Digital counter intercom with touch-sensitive pad and headset mic HD-1022 loop cable and magnetic loop amplifier, suitable for hearing impaired people	<u>C3</u>	1'225.-

	<p><b>OP-6515H</b></p> <p>Digital counter intercom with touch-sensitive pad and wireless mic customer side. English message.</p>	<p><u>C3</u></p>	<p>1'045.-</p>
	<p><b>OP-6515HB</b></p> <p>Digital counter intercom with touch-sensitive pad, wireless mic customer side and loop cable and magnetic loop amplifier, suitable for hearing impaired people</p>	<p><u>C3</u></p>	<p>1'275.-</p>
	<p><b>OP-6515HK</b></p> <p>Digital counter intercom with touch-sensitive pad, wireless mic customer side and headset mic HD-1022</p>	<p><u>C3</u></p>	<p>1'165.-</p>
	<p><b>OP-6515HBK</b></p> <p>Digital counter intercom with touch-sensitive pad wireless mic customer side and headset mic HD-1022 loop cable and magnetic loop amplifier, suitable for hearing impaired people</p>	<p><u>C3</u></p>	<p>1'395.-</p>

# UHF Audio Transmission System

	<b>OP-10STX</b>	UHF stationary transmitter 863-865MHz, 16 channels, 2 mixable inputs	<u>C3</u>	630.-
	<b>OP-10T</b>	UHF 863-865 MHz portable transmitter, lithium-ion battery with 14 hours autonomy	<u>C3</u>	270.-
	<b>OP-8TH</b>	Hand-held electret microphone transmitter 863-865 MHz	<u>C3</u>	310.-
	<b>OP-10R</b>	UHF portable receiver 863-865 MHz accumulator, lithium-ion battery with 14 hours autonomy	<u>C3</u>	315.-
	<b>OP-10SRX</b>	UHF fixed receiver 863 - 865MHz diversity.	<u>C3</u>	715.-
	<b>OP-10CH2</b>	Charging station for 2 devices	<u>C3</u>	120.-
	<b>OP-10CH18</b>	Charging and transportation suitcase for 18 devices from the OPUS10 range	<u>C3</u>	890.-
	<b>OP-10CH36</b>	Charging and transportation suitcase for 36 devices from the OPUS10 range.	<u>C3</u>	1'660.-

	OP-CAS	18" universal storage suitcase, with pre-cutting foam. Waterproof	<u>C3</u>	165.-
	OP-CAS1	10.5" storage suitcase with protection foam	<u>C3</u>	115.-
	OP-CAS4	Rigid suitcase, waterproof - 720 x 430 x 180 mm	<u>C3</u>	330.-
	OP-CAS12	18" storage case with multi-socket AC jack connector to supply OP-10MULTI and OP-10M12, with pre-cutting foam for 6x OP-10CH2 and 12x OP-R and accessories	<u>C3</u>	280.-
	OP-SBAG	Soft waterproof bag 200x180x100mm	<u>C3</u>	60.-

Ersetzt alle bisherigen Preislisten.

Remplace et annule les précédentes listes de prix.

Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.

Articles avec code client gris sont des nouveautés ou ont changé de prix.

Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!

Articles avec code client souligné demandez leur disponibilité!