



Line Array Systems	WPM / WPC / WPS	Link
Torus Line Array Systems	T1215 / T1230 / T820	Link
	Zubehör zu T12xx / T820	Link
FlexPoint	2-Weg System ab 4" bis 15", (passiv)	Link
TH Series	THH / THV / THS	Link
Subwoofers	passiv	Link
	aktiv	Link
Stage Monitors	LE100 / LE200 / XE300 / XE500	Link
BlacklineXP Series	2-Weg System ab 12", 15", (aktiv)	Link
Blackline Q Series	2-Weg System ab 8" bis 15", (passiv)	Link
	Zubehör	Link
O-Line (Line Array Installation)	Line Array	Link
CDD Series (passiv, aktiv)	2-way System ab 5.25" bis 15", schwarz/weiss (passiv)	Link
	Zubehör zu CDD Serie	Link
	DSP und Dante 8", 12", 15", schwarz/weiss (aktiv)	Link
Adorn Series	2-way System 4", 5", 8", schwarz/weiss	Link
Ceiling Series	Deckenlautsprecher	Link
Amplifiers	iKON Serie / VIA	Link
Controllers	DX-Serie	Link

* GoWild (kein BOSE)-Artikel

Wavefront Precision Series

	WPM	2-way, passive line array element, LF: 2x6.5" / HF: 3x1.4", 16Ohm, frequency response 76Hz-18kHz +/- 3dB, max. SPL 130dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)500mm x (H)185mm x (D)377mm, 14Kg	<u>C3</u>	3'575.-
	WPM-W	Dito, white	<u>C3</u>	3'575.-
	WPS	3-way, passive line array element, LF: 2x8" / MF: 4x4" / HF: 4x 1", 6Ohm, frequency response 70Hz-18kHz +/- 3dB, max. SPL 133dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)650mm x (H)261mm x (D)400mm, 27Kg	<u>C3</u>	5'525.-
	WPS-W	Dito, white	<u>C3</u>	5'525.-
	WPC	3-way, bi-amp line array element, LF: 2x10" / MF: 2x5" / HF: 4x 0.7", 8Ohm, frequency response 65Hz-18kHz +/- 3dB, max. SPL 135dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)772mm x (H)319mm x (D)421mm, 35Kg	<u>C3</u>	7'150.-
	WPC-W	Dito, white	<u>C3</u>	7'150.-
	WPL	3-way, bi-amp line array element, LF: 2x12" / MF: 2x6.5" / HF: 3x 1", 8Ohm, frequency response 52Hz-18kHz +/- 3dB, max. SPL LF: 135dB / MF: 140dB / HF: 145dB, 90° hor. / 7.5° vert, side pocket handles, (W)1136mm x (H)371mm x (D)526mm, 64Kg	<u>C3</u>	11'695.-

Diverses Zubehör wie: Tour/Install Flybar, Dolly System, Transition Frame etc. auf Anfrage!

Torus

	T820	2-way, passive, 20° fixed angle array cabinet, LF: 8" / HF: 2x1", 200W AES @80hm, frequency response 70Hz-18kHz +/- 3dB, max. SPL 126dB, 120° hor. / 20° vert, (W)500mm x (H)257mm x (D)320mm, 14Kg	<u>C3</u>	2'795.-
	T1215	2-way, passive, 15° fixed angle array cabinet, LF: 12" / HF: 3x1", 400W AES @80hm, frequency response 65Hz-18kHz +/- 3dB, max. SPL 134dB, 60/75/90° hor. / 15° vert, (W)650mm x (H)369mm x (D)452mm, 31Kg	<u>C3</u>	4'225.-
	T1230	2-way, passive, 30° fixed angle array cabinet, LF: 12" / HF: 3x1", 400W AES @80hm, frequency response 65Hz +/- 3dB, max. SPL 132dB, 60/75/90° hor. / 30° vert, (W)650mm x (H)350mm x (D)442mm, 26Kg	<u>C3</u>	4'225.-

Torus - Accessories

	POLERIG20	Pole-mount bracket for T8xx cabinets	<u>C3</u>	390.-
	POLERIG1530	Pole-mount bracket for T12xx cabinets	<u>C3</u>	520.-
	SBAR40	Flying Bracket for up to two T8xx or a single T12xx	<u>C3</u>	260.-
	HRIG100	Modular flying bar for horizontal arrays, maximum 3x T8xx or 3x T12xx	<u>C3</u>	650.-
	GSRIG20	Ground-stack frame for T8xx cabinets to SXCF115	<u>C3</u>	975.-
	GSRIG1530	Dito, for T12xx cabinets to SXCF118	<u>C3</u>	1'295.-
	T8GRID	Flying frame for 6x T8xx arrays and transition frame for SXCF115 to T8xx array	<u>C3</u>	2'235.-
	T12GRID	Flying frame for T12xx arrays	<u>C3</u>	2'860.-
	T12TRIG	Transition frame for SXCF118 to T12xx array	<u>C3</u>	1'625.-
	T8PB	Simple rigging bar for T8 cabinet, up to 6x T8xx	<u>C3</u>	910.-
	T12PB	Simple rigging bar for T12 cabinet	<u>C3</u>	910.-
	ASF20071	Wind-up telescopic pole for T8xx and T12xx cabinet	<u>C3</u>	295.-

Lautsprecher sowie Zubehör auch in weiss erhältlich!

FlexPoint

	FP4	2-way, passive, coaxial, miniature point source loudspeaker, LF: 4" / HF: 1.25", 60W AES @16Ohm, frequency response 142Hz-18kHz +/- 3dB, max. SPL 102dB, 110° conical, M6 inserts, (W)130mm x (H)130mm x (D)126mm, 1.9Kg	<u>C3</u>	620.-
	FP6	2-way, passive, coaxial, compact point source loudspeaker, LF: 6" / HF: 1.75", 150W AES @16Ohm, frequency response 73Hz-20kHz +/- 3dB, max. SPL 113dB, 100° hor. / 80° vert (user-rotatable), M10 / M6 inserts, (W)321mm x (H)220mm x (D)197mm, 5.5Kg	<u>C3</u>	1'170.-
	FP8	2-way, passive, coaxial, compact point source loudspeaker, LF: 8" / HF: 2", 250W AES @8Ohm, frequency response 63Hz-18kHz +/- 3dB, max. SPL 118dB, 90° hor. / 70° vert (user-rotatable), M10 / M6 inserts, (W)376mm x (H)280mm x (D)265mm, 9.3Kg	<u>C3</u>	1'820.-
	FP12	2-way, passive, coaxial, compact point source loudspeaker, LF: 12" / HF: 3", 350W AES @8Ohm, frequency response 55Hz-20kHz +/- 3dB, max. SPL 122dB, 90° hor. / 60° vert (user-rotatable), M10 / M6 inserts, (W)521mm x (H)390mm x (D)346mm, 17.5Kg	<u>C3</u>	2'730.-
	FP15	2-way, passive, coaxial, compact point source loudspeaker, LF: 15" / HF: 3.5", 500W AES @8Ohm, frequency response 50Hz-20kHz +/- 3dB, max. SPL 126dB, 80° hor. / 50° vert (user-rotatable), M10 / M8 inserts, (W)601mm x (H)460mm x (D)420mm, 27.4Kg	<u>C3</u>	3'770.-

FlexPoint - Accessories

	FP4Y-B	FP4 Touring & Install Yoke	<u>C3</u>	65.-
	FP6YLT-B	FP6 Landscape Touring Yoke	<u>C3</u>	335.-
	FP8YLT-B	Dito, FP8	<u>C3</u>	395.-
	FP12YLT-B	Dito, FP12	<u>C3</u>	545.-
	FP15YLT-B	Dito, FP15	<u>C3</u>	650.-
	FP6YPT-B	FP6 Portrait Touring Yoke	<u>C3</u>	335.-
	FP8YPT-B	Dito, FP8	<u>C3</u>	395.-
	FP12YPT-B	Dito, FP12	<u>C3</u>	545.-
	FP15YPT-B	Dito, FP15	<u>C3</u>	650.-
	FP6YLI-B	FP6 Landscape Install Yoke	<u>C3</u>	270.-
	FP8YLI-B	Dito, FP8	<u>C3</u>	345.-
	FP12YLI-B	Dito, FP12	<u>C3</u>	410.-
	FP15YLI-B	Dito, FP15	<u>C3</u>	545.-
	FP6YPI-B	FP6 Portrait Install Yoke	<u>C3</u>	270.-
	FP8YPI-B	Dito, FP8	<u>C3</u>	345.-
	FP12YPI-B	Dito, FP12	<u>C3</u>	410.-
	FP15YPI-B	Dito, FP15	<u>C3</u>	545.-

O-Line 4 Pack

	O-Line 2 x 3.5" scalable, 2-way, micro-line array, 4 cabinet array (Picture: 2 x Omniline 4 pack - price per 4-pack!) Tech. spec. per module: 50W AES, 200W peak, 84-92 dB 1W/1m, 100° hor., 5° vert., 16Ω, light grey, Tech. spec. per 4 pack: 200W AES, 800W peak, 96dB 1W/1m, 4Ω, 14.4kg	<u>C3</u>	2'990.-
---	--	------------------	----------------

Accessories

	ASF20023 Flying Bracket	<u>C3</u>	455.-
	ASF20021 Wall Bracket for 1 x 4-Pack O-Line Array	<u>C3</u>	520.-
	ASF20022 Wall Bracket for 2-3 x 4-Pack O-Line Arrays	<u>C3</u>	1'040.-

TH Series

	THH 3-way, bi-amp trapezoid hybrid fully horn loaded, LF: 15" / MF: 10" / HF: 1", LF: 750W AES @80hm, MF+HF: 300W AES @80hm, frequency response 50Hz-18kHz +/- 3dB, max. SPL 133dB, 70° hor. / 40° vert, pocket handle, M10 inserts, (W)1067mm x (H)558mm x (D)780mm, 77Kg	<u>C3</u>	5'850.-
	THV Dito, Vertical	<u>C3</u>	5'850.-
	THS 3-way, bi-amp triaxial point source loudspeaker, LF: 15" / MF: 1.4" / HF: 1.4", LF: 800W AES @80hm, MF+HF: 110W AES @80hm, frequency response 54Hz-18kHz +/- 3dB, max. SPL 129dB, 85° hor. / 50° vert, pocket handle, M10 inserts, (W)511mm x (H)710mm x (D)511mm, 35.6Kg	<u>C3</u>	5'200.-
	THSYLT-B Landscape Touring Yoke	<u>C3</u>	650.-
	THSYLI-B Landscape Install Yoke	<u>C3</u>	585.-
	THSYPT-B Portrait Touring Yoke	<u>C3</u>	715.-
	THSYPI-B Portrait Install Yoke	<u>C3</u>	585.-

Stage Monitors

	LE100	2-way, passive coaxial differential dispersion, LF: 12" / HF: 1", 300W AES @8Ohm, frequency response 78Hz-20kHz +/- 3dB, max. SPL 129dB, 110° hor. / 60° vert, pocket handle, M8 inserts, pole mounting, protective rubber feet (W)490mm x (H)302mm x (D)472mm, 18Kg	<u>C3</u>	1'950.-
	LE200	2-way, passive coaxial differential dispersion, LF: 15" / HF: 1.4", 400W AES @8Ohm, frequency response 78Hz-20kHz +/- 3dB, max. SPL 133dB, 110° hor. / 60° vert, pocket handle, M8 inserts, pole mounting, protective rubber feet (W)610mm x (H)364mm x (D)562mm, 26Kg	<u>C3</u>	2'340.-
	XE300	2-way, passive/bi-amp coaxial differential dispersion, LF: 12" / HF: 1.4", LF: 350W AES @6Ohm, HF: 80W AES @8Ohm, frequency response 67Hz-18kHz +/- 3dB, max. SPL 139dB, 60° hor. / 90° vert, pocket handle, M8 inserts, protective rubber feet, (W)550mm x (H)290mm x (D)470mm, 19Kg	<u>C3</u>	3'250.-
	XE500	2-way, passive/bi-amp coaxial differential dispersion, LF: 15" / HF: 1.4", LF: 550W AES @4Ohm, HF: 80W AES @8Ohm, frequency response 62Hz-18kHz +/- 3dB, max. SPL 143dB, 60° hor. / 70° vert, bar handles, M8 inserts, protective rubber feet, (W)635mm x (H)364mm x (D)583mm, 19Kg	<u>C3</u>	4'290.-

CDD Live - aktiv

	CDD-LIVE8B	2-way, powered ultra-compact coaxial differential dispersion system, LF: 8" / HF: 1", peak 1300W, continuous 650W, frequency response 70Hz-20kHz +/- 3dB, max. SPL 123dB, 110° hor. / 60° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)258mm x (H)428mm x (D)254mm, 14Kg, Dante, DSP	<u>C3</u>	2'860.-
	CDD-LIVE8W	Dito, white	<u>C3</u>	2'860.-
	CDD-LIVE12B	2-way, powered ultra-compact coaxial differential dispersion system, LF: 12" / HF: 1", peak 2500W, continuous 1250W, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 110° hor. / 60° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)359mm x (H)580mm x (D)373mm, 28Kg, Dante, DSP	<u>C3</u>	3'640.-
	CDD-LIVE12W	Dito, white	<u>C3</u>	3'640.-
	CDD-LIVE15B	2-way, powered ultra-compact coaxial differential dispersion system, LF: 15" / HF: 1.4", peak 2500W, continuous 1250W, frequency response 55Hz-20kHz +/- 3dB, max. SPL 132dB, 110° hor. / 60° vert, (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)427mm x (H)696mm x (D)422mm, 37Kg, Dante, DSP	<u>C3</u>	4'550.-
	CDD-LIVE15W	Dito, white	<u>C3</u>	4'550.-

CDD Live – Accessories

	CDDCB6/8B	Ceiling bracket for CDD-Live 8, black	C3	195.–
	CDDCB6/8W	Dito, white	C3	195.–
	WB6/8B	Wall bracket for CDD-Live 8, black, weatherised	C3	70.–
	WB6/8W	Dito, white	C3	70.–
	WB10/12B	Wall bracket for CDD-Live 12, black, weatherised	C3	85.–
	WB10/12W	Dito, white	C3	85.–
	CDDLUB8B	Universal bracket for CDD-Live 8, black	<u>C3</u>	325.–
	ASF20046	Universal bracket for CDD-Live 12, black	<u>C3</u>	585.–
	ASF20048	Universal bracket for CDD-Live 15, black	<u>C3</u>	585.–
	CDDL YA8B	Yoke assembly for CDD-Live 8, black	<u>C3</u>	295.–
	CDDL YA8W	Dito, white	<u>C3</u>	295.–
	CDDL YA12B	Yoke assembly for CDD-Live 12, black	<u>C3</u>	335.–
	CDDL YA12W	Dito, white	<u>C3</u>	325.–
	CDDL YA15B	Yoke assembly for CDD-Live 15, black	<u>C3</u>	390.–
	CDDL YA15W	Dito, white	<u>C3</u>	390.–
	HTKCT05	8mm shouldered eye bolt for CDD-Live 8, 12, 15	<u>C3</u>	40.– (Stück)
	ASF20045	Universal 35mm pole mount adaptor	<u>C3</u>	65.–
	ASF20071	Wind-up telescopic pole	<u>C3</u>	295.–

Diverses Zubehör wie: Transit Cover, Rain Kit Upgrade auf Anfrage!

CDD Series – passiv

VPE

	CDD5B	2-way, passive ultra compact differential dispersion system, nLF: 5.25" / HF: 0.75", 100W AES @80hm, frequency response 100Hz-20kHz +/- 3dB, max. SPL 116dB, 120° hor. / 80° vert, (user-rotatable), M6 inserts, (W)160mm x (H)230mm x (D)149mm, 3Kg, incl. wall bracket	2	C3	315.–
	CDD5W	Dito, white	2	C3	315.–
	CDD5BTX-WR	Dito, 6/12.5/25W@100V, black, weatherised	2	C3	390.–
	CDD5WTX-WR	Dito, 6/12.5/25W@100V, white, weatherised	2	C3	390.–
	CDD5BTX-MAR	For cruise ships and seaside resort applications, black	2	C3	520.–
	CDD5WTX-MAR	Dito, white	2	C3	520.–
	CDD6B	2-way, passive ultra compact differential dispersion system, LF: 6.5" / HF: 1", 150W AES @80hm, frequency response 80Hz-20kHz +/- 3dB, max. SPL 119dB, 110° hor. / 80° vert, (user-rotatable), M6 inserts, (W)210mm x (H)325mm x (D)210mm, 5.7Kg	2	C3	520.–
	CDD6W	Dito, white	2	C3	520.–
	CDD6BTX-WR	Dito, 12.5/25/50W@100V, black, weatherised	2	C3	585.–
	CDD6WTX-WR	Dito, 12.5/25/50W@100V, white, weatherised	2	C3	585.–
	CDD6BTX-MAR	For cruise ships and seaside resort applications, black	2	C3	780.–
	CDD6WTX-MAR	Dito, white	2	C3	780.–
	CDD8B	2-way, passive ultra compact differential dispersion system, LF: 8" / HF: 1", 200W AES @80hm, frequency response 70Hz-20kHz +/- 3dB, max. SPL 119dB, 110° hor. / 60° vert, (user-rotatable), M6 inserts, (W)256mm x (H)410mm x (D)252mm, 9.5Kg		C3	910.–
	CDD8W	Dito, white		C3	910.–
	CDD8B-WR	Dito, black, weatherised		C3	1'105.–
	CDD8W-WR	Dito, white, weatherised		C3	1'105.–
	CDD8BTX	Dito, 15/30/60/120W@100V, 11.1Kg, black		C3	1'050.–
	CDD8WTX	Dito, white		C3	1'050.–
	CDD8BTX-WR	Dito, black, weatherised		C3	1'245.–
	CDD8WTX-WR	Dito, white, weatherised		C3	1'245.–
	CDD8BTX-MAR	For cruise ships and seaside resort applications, black		C3	1'540.–
	CDD8WTX-MAR	Dito, white		C3	1'540.–

	CDD10B	2-way, passive ultra compact differential dispersion system, LF: 10" / HF: 1", 250W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 126dB, 110° hor. / 60° vert (user-rotatable), M6 inserts, (W)323mm x (H)513mm x (D)310mm, 15.3Kg	C3	1'365.-
	CDD10W	Dito, white	C3	1'365.-
	CDD10B-WR	Dito, black, weatherised	C3	1'625.-
	CDD10W-WR	Dito, white, weatherised	C3	1'625.-
	CDD10BTX	Dito, 15/30/60/120W@100V, 16.9Kg, black	C3	1'560.-
	CDD10WTX	Dito, white	C3	1'560.-
	CDD10BTX-WR	Dito, black, weatherised	C3	1'885.-
	CDD10WTX-WR	Dito, white, weatherised	C3	1'885.-
	CDD10BTX-MAR	For cruise ships and seaside resort applications, black	C3	2'470.-
	CDD10WTX-MAR	Dito, white	C3	2'470.-
	CDD12B	2-way, passive ultra compact differential dispersion system, LF: 12" / HF: 1", 300W AES @8Ohm, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 110° hor. / 60° vert (user-rotatable), M8 inserts, (W)360mm x (H)560mm x (D)350mm, 19Kg	C3	1'950.-
	CDD12W	Dito, white	C3	1'950.-
	CDD12B-WR	Dito, black, weatherised	C3	2'275.-
	CDD12W-WR	Dito, white, weatherised	C3	2'275.-
	CDD12B-MAR	For cruise ships and seaside resort applications, black	C3	3'120.-
	CDD12W-MAR	Dito, white	C3	3'120.-
	CDD15B	2-way, passive ultra compact differential dispersion system, LF: 15" / HF: 1.4", 400W AES @8Ohm, frequency response 55Hz-18kHz +/- 3dB, max. SPL 132dB, 110° hor. / 60° vert (user-rotatable), M8 inserts, (W)432mm x (H)685mm x (D)413mm, 19Kg	C3	2'470.-
	CDD15W	Dito, white	C3	2'470.-
	CDD15B-WR	Dito, black, weatherised	C3	2'925.-
	CDD15W-WR	Dito, white, weatherised	C3	2'925.-
	CDD15B-MAR	For cruise ships and seaside resort applications, black	C3	3'900.-
	CDD15W-MAR	Dito, white	C3	3'900.-

CDD Series - Accessories

	WB6/8B	Wall bracket for CDD6Bxx – CDD8Bxx, black, weatherised	C3	70.–
	WB6/8W	Dito, white	C3	70.–
	WB6/8B-MAR	Wall bracket for CDD6BTX-MAR – CDD8BTX-MAR, black	<u>C3</u>	390.–
	WB6/8W-MAR	Dito white	<u>C3</u>	390.–
	WB10/12B	Wall bracket for CDD10Bxx – CDD12Bxx, black, weatherised	C3	85.–
	WB10/12W	Dito white	C3	85.–
	WB10/12B-MAR	Wall bracket for CDD10BTX-MAR – CDD12BTX-MAR, black	C3	455.–
	WB10/12W-MAR	Dito white	C3	455.–
	WB15B	Wall bracket for CDD15Bxx, black, weatherised	<u>C3</u>	130.–
	WB15W	Dito white	<u>C3</u>	130.–
	CDDCB5B-WR	Ceiling bracket for CDD5Bxx, black, weatherised	C3	90.–
	CDDCB5W-WR	Dito, white	C3	90.–
	CDDCB6/8B-WR	Ceiling bracket for CDD6Wxx – CDD8Wxx, black, weatherised	C3	195.–
	CDDCW6/8W-WR	Dito, white	C3	195.–
	CDDY10B	Yoke assembly for CDD10Bxx, black, weatherised	C3	325.–
	CDDY10W	Dito, white	C3	325.–
	CDDY12B	Yoke assembly for CDD12Bxx, black, weatherised	C3	390.–
	CDDY12W	Dito, white	C3	390.–
	CDDY15B	Yoke assembly for CDD15Bxx, black, weatherised	C3	420.–
	CDDY15W	Dito, white	C3	420.–
	HTKCT05	8mm shouldered eye bolt for CDD 10, 12, 15	<u>C3</u>	40.– (Stück)

Blackline Q Series – passiv

	Q8B	2-way, passive ultra compact system, LF: 8" / HF: 1", 200W AES @80hm, frequency response 67Hz-17kHz +/- 3dB, max. SPL 121dB, 90°-110° hor. / 50° vert. (user-rotatable), M6/M8 inserts, pocket handle, pole mounting, (W)236mm x (H)500mm x (D)250mm, 8Kg	<u>C3</u>	650.–
	Q10B	2-way, passive ultra compact system, LF: 10" / HF: 1", 250W AES @80hm, frequency response 63Hz-17kHz +/- 3dB, max. SPL 125dB, 90°-110° hor. / 50° vert. (user-rotatable), M6/M8 inserts, pocket handle, pole mounting, (W)300mm x (H)545mm x (D)310mm, 15Kg	<u>C3</u>	845.–
	Q12B	2-way, passive ultra compact system, LF: 12" / HF: 1", 300W AES @80hm, frequency response 65Hz-17kHz +/- 3dB, max. SPL 127dB, 90°-110° hor. / 50° vert. (user-rotatable), M8 inserts, pocket handle, pole mounting, (W)358mm x (H)600mm x (D)321mm, 18Kg	<u>C3</u>	975.–
	Q15B	2-way, passive ultra compact system, LF: 15" / HF: 1.4", 800W AES @80hm, frequency response 51Hz-17kHz +/- 3dB, max. SPL 133dB, 70°-90° hor. / 50° vert. (user-rotatable), M8 inserts, pocket handle, pole mounting, (W)420mm x (H)695mm x (D)400mm, 34Kg	<u>C3</u>	1'555.–
	Q44B	2-way, passive compact column speaker, LF: 4x4" / HF: 1", 200W AES @80hm, frequency response 82Hz-17kHz +/- 3dB, max. SPL 119dB, 100°-120° hor. / 40° vert. M6/M8 inserts, pocket handle, pole mounting, (W)150mm x (H)800mm x (D)187mm, 7.5Kg	<u>C3</u>	455.–
	Q44W	Dito, white	<u>C3</u>	455.–
	Q26B	2-way, passive compact column speaker, LF: 2x6" / HF: 1", 300W AES @80hm, frequency response 69Hz-17kHz +/- 3dB, max. SPL 125dB, 100°-120° hor. / 40° vert. M6/M8 inserts, pocket handle, pole mounting, (W)193mm x (H)670mm x (D)218mm, 9.5Kg	<u>C3</u>	520.–
	Q26W	Dito, white	<u>C3</u>	520.–

BlacklineXP Series – Powered


	XP12	2-way, powered compact system, LF: 12" / HF: 1", peak 1300W, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 80° hor. / 50° vert. (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)358mm x (H)574mm x (D)318mm, 18Kg, DSP	C3	1'725.–
	XP15	2-way, powered compact system, LF: 15" / HF: 1", peak 1300W, frequency response 55Hz-20kHz +/- 3dB, max. SPL 131dB, 80° hor. / 50° vert. (user-rotatable), pocket handle, M8 inserts, pole mounting, (W)427mm x (H)690mm x (D)407mm, 26Kg, DSP	C3	2'015.–

BlacklineQ / XP Series – Accessories

	Q44YP-B	Q44 Portrait Install Yoke, black	<u>C3</u>	195.–
	Q44YP-W	Dito, white	<u>C3</u>	195.–
	Q26YP-B	Q26 Portrait Install Yoke, black	<u>C3</u>	235.–
	Q26YP-W	Dito, white	<u>C3</u>	235.–
	Q8YP-B	Q8 Portrait Install Yoke, black	<u>C3</u>	195.–
	Q10YP-B	Q10 Portrait Install Yoke, black	<u>C3</u>	230.–
	Q12YP-B	Q12 Portrait Install Yoke, black	<u>C3</u>	260.–
	Q15YP-B	Q15 Portrait Install Yoke, black	<u>C3</u>	325.–
	WB6/8B	Wall bracket for Q8B – Q44B – Q26B – XP12, black, weatherised	C3	70.–
	WB6/8W	Dito, white for Q44W – Q26W	C3	70.–
	WB10/12B	Wall bracket for Q10B – Q12B – XP12, black, weatherised	C3	85.–
	WB15B	Wall bracket for Q15B black, weatherised	<u>C3</u>	130.–
	HTKCT04	Pole for BlacklineQ – XP12 – XP15	<u>C3</u>	30.–
	HTKCT05	8mm shouldered eye bolt for Q8 – Q10 – Q12 – Q15 – XP12 – XP15	<u>C3</u>	40.– (Stück)

Adorn – Series				VPE	
 	A40B	2-way, passive ultra compact system, LF: 4" / HF: 0.75", 40W AES @16Ohm, frequency response 98Hz-17kHz +/- 3dB, max. SPL 109dB, 110° hor. / 80° vert, (W)124mm x (H)200mm x (D)144mm, 1.7Kg, incl. wall bracket	2	C3	135.–
	A40W	Dito, white	2	C3	135.–
	A40TB	Dito, 2.5/5/10W@100V, 2.1Kg, black	2	C3	170.–
	A40TW	Dito, white	2	C3	170.–
 	A55B	2-way, passive ultra compact system, LF: 5.25" / HF: 0.75", 50W AES @16Ohm, frequency response 90Hz-17kHz +/- 3dB, max. SPL 109dB, 110° hor. / 80° vert, (W)152mm x (H)245mm x (D)140mm, 2.1Kg, incl. wall bracket	2	C3	185.–
	A55W	Dito, white	2	C3	185.–
	A55TB	Dito, 7.5/15/30W@100V, 2.8Kg, black	2	C3	220.–
	A55TW	Dito, white	2	C3	220.–
 	A80TB	2-way, passive compact system, LF: 8" / HF: 1", 200W AES @8Ohm, 15/30/60W@100V frequency response 63Hz-17kHz +/- 3dB, max. SPL 120dB, 90° hor. / 50° vert, (W)246mm x (H)421mm x (D)233mm, 9Kg, incl. wall bracket (WB6/8)		<u>C3</u>	455.–
	A80TW	Dito, white		<u>C3</u>	455.–
	AIPKIT-B	IP44 Connector cover for A40 and A55 Series, black	2	<u>C3</u>	15.–
	AIPKIT-W	Dito, white	2	<u>C3</u>	15.–
Adorn Series – Accessories					
	CDDCB5B-WR	Ceiling bracket for A40xx – A55xx, black, weatherised		C3	90.–
	CDDCB5W-WR	Dito, white		C3	90.–

Subwoofer – passiv

	SX110B	slimline, direct radiating subwoofer, 10", 250W AES @80hm, frequency response 50Hz-150Hz +/- 3dB, max. SPL 127dB, omnidirectional, M8 inserts, (W)417mm x (H)297mm x (D)415mm, 12Kg	<u>C3</u>	585.–
	SX110W	Dito, white	<u>C3</u>	585.–
	SX210B	slimline, dual-driver direct radiating subwoofer, 2x 10", 500W AES @40hm, frequency response 50Hz-150Hz +/- 3dB, max. SPL 133dB, omnidirectional, M8 inserts, bar handles, (W)718mm x (H)295mm x (D)465mm, 20Kg	<u>C3</u>	910.–
	SX210W	Dito, white	<u>C3</u>	910.–
	Q210B	slimline, portable dual-driver subwoofer, 2x 10", 400W AES @40hm, frequency response 49Hz-100Hz +/- 3dB, max. SPL 124dB, omnidirectional, M8 inserts, bar handles, pole mounting, (W)296mm x (H)718mm x (D)462mm, 20Kg	<u>C3</u>	975.–
	Q210W	Dito, white	<u>C3</u>	975.–
	SX112B	ultra compact, direct radiating subwoofer 12", 400W AES @80hm, frequency response 48Hz-150Hz +/- 3dB, max. SPL 132dB, omnidirectional, M10 inserts, (W)487mm x (H)390mm x (D)410mm, 21.5Kg	<u>C3</u>	1'010.–
	SX112W	Dito, white	<u>C3</u>	1'010.–
	SX112-W-MAR	For cruise ships and seaside resort applications, white	<u>C3</u>	2'535.–
	SX212B	compact, dual-driver direct radiating subwoofer 2x 12", 800W AES @40hm, frequency response 48Hz-150Hz +/- 3dB, max. SPL 138dB, omnidirectional, M10 inserts, (W)872mm x (H)390mm x (D)437mm, 39Kg	<u>C3</u>	1'430.–
	SX212W	Dito, white	<u>C3</u>	1'430.–
	SX115	compact, direct radiating subwoofer, 15", 1000W AES @80hm, frequency response 45Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, bar handles, pole mounting, provision for castors, (W)500mm x (H)451mm x (D)678mm, 36.5Kg	<u>C3</u>	1'950.–
	SX215	compact, dual-driver direct radiating subwoofer, 2x 15", 1600W AES @40hm, frequency response 45Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, provision for castors, (W)961mm x (H)463mm x (D)679mm, 64Kg	<u>C3</u>	3'250.–

	SXC115	compact, cardioid subwoofer, 15" 1000W AES @80hm, 12" 800W AES @80hm, frequency response 44Hz-150Hz +/- 3dB, max. SPL 137dB, cardioid, M10 inserts, bar handles, pole mounting, provision for castors, (W)500mm x (H)550mm x (D)811mm, 53Kg	<u>C3</u>	3'895.-
	SXC115W	Dito, white	<u>C3</u>	3'895.-
	SXCF115	Dito, flown, (W)500mm x (H)552mm x (D)810mm, 61Kg	<u>C3</u>	6'045.-
	Q118B	compact, portable subwoofer, 18", 800W AES @80hm, frequency response 38Hz-100Hz +/- 3dB, max. SPL 130dB, omnidirectional, M8/M10 inserts, bar handles, pole mounting, (W)530mm x (H)606mm x (D)690mm, 45Kg	C3	1'295.-
	SX118B	compact, direct radiating subwoofer, 18", 1000W AES @80hm, frequency response 47Hz-150Hz +/- 3dB, max. SPL 138dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)600mm x (H)509mm x (D)632mm, 43.5Kg	<u>C3</u>	3'250.-
	SX118W	Dito, white	<u>C3</u>	3'250.-
	SX118B-MAR	For cruise ships and seaside resort applications, black	<u>C3</u>	3'900.-
	SX118W-MAR	Dito, white	<u>C3</u>	3'900.-
	SXC118B	compact, cardioid subwoofer, 18" 1000W AES @80hm, 14" 800W AES @80hm, frequency response 43Hz-150Hz +/- 3dB, max. SPL 140dB, cardioid, M10 inserts, bar handles, pole mounting, provision for castors, (W)650mm x (H)603mm x (D)812mm, 73Kg	<u>C3</u>	4'875.-
	SXC118W	Dito, white	<u>C3</u>	4'875.-
	SXCF118B	Dito, flown, (W)650mm x (H)611mm x (D)812mm, 75Kg	<u>C3</u>	7'150.-
	Q218	dual-driver direct radiating subwoofer, 2x 18", 1600W AES @40hm, frequency response 38Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, M8/M10 inserts, bar handles, pole mounting, provision for castors, (W)536mm x (H)1206mm x (D)690mm, 82Kg	<u>C3</u>	2'595.-
	SX218B	dual-driver direct radiating subwoofer, 2x 18", 2000W AES @2x 80hm, frequency response 35Hz-200Hz +/- 3dB, max. SPL 144dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1093mm x (H)537mm x (D)792mm, 102Kg	<u>C3</u>	5'525.-
	SX218W	Dito, white	<u>C3</u>	5'525.-
	SX218B-MAR	For cruise ships and seaside resort applications, black	<u>C3</u>	7'535.-
	SX218W-MAR	Dito, white	<u>C3</u>	7'535.-
	SXH218	hybrid® horn/reflex flown dual-driver subwoofer, 2x 18", 3000W AES @40hm, frequency response 32Hz-200Hz +/- 3dB, max. SPL 148dB, omnidirectional, bar handles, (W)1112mm x (H)609mm x (D)1151mm, 116Kg	<u>C3</u>	8'770.-
	SXHF218	Dito, flown, (W)1148mm x (H)604mm x (D)1155mm, 138Kg	<u>C3</u>	11'045.-

Diverses Zubehör wie: Transit Cover, Rain Kit Upgrade auf Anfrage!

Subwoofer – powerd

	XP118	powerd compact direct radiating subwoofer, 18", peak 2000W, frequency response 52Hz-150Hz +/- 3dB, max. SPL 137dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)600mm x (H)507mm x (D)632mm, 46.5Kg	<u>C3</u>	2'080.–
	SXP118B	powerd compact direct radiating subwoofer, 18", peak 2000W, frequency response 47Hz-150Hz +/- 3dB, max. SPL 135dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)662mm x (H)536mm x (D)640mm, 44Kg, Dante, DSP	<u>C3</u>	5'200.–
	SXP118W	Dito, white	<u>C3</u>	5'200.–
	SXP218B	powerd dual-driver compact direct radiating subwoofer, 2x 18", peak 4000W, frequency response 35Hz-150Hz +/- 3dB, max. SPL 143dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1085mm x (H)537mm x (D)792mm, 101Kg, Dante, DSP	<u>C3</u>	7'795.–
	SXP218W	Dito, white	<u>C3</u>	7'795.–

Subwoofer – Accessories

	HTKCT05	8mm shouldered eye bolt for SX110, SX210, Q210,	<u>C3</u>	40.– (Stück)
	HTKCT06	10mm shouldered eye bolt for SX112, SX212, SX118, SXC118, SX218, SXP118, SXP218	<u>C3</u>	45.– (Stück)
	ASF20071	Wind-up telescopic pole for SX118, SXC118, SX218, SXP118, SXP218	<u>C3</u>	295.–

Ceiling Series

VPE

	C4.8T	2-way, passive high performance ceiling system, LF: 4" / HF: 0.8", 40W AES @16Ohm, 3/6/12.5/25W@100V, frequency response 100Hz-20kHz +/- 3dB, max. SPL 108dB, 180° conical, cut out 178mm, Ø 205mm x (D)131mm, 2.6Kg	2	C3	195.-
	C6.8T	2-way, passive high performance ceiling system, LF: 6.5" / HF: 0.8", 75W AES @16Ohm, 5/10/20/40W@100V, frequency response 90Hz-20kHz +/- 3dB, max. SPL 112dB, 180° conical, cut out 224mm, Ø 260mm x (D)181mm, 3.5Kg	2	C3	275.-
	C8.1T	2-way, passive high performance ceiling system, LF: 8" / HF: 1", 125W AES @16Ohm, 7.5/15/30/60W@100V, frequency response 80Hz-18kHz +/- 3dB, max. SPL 116dB, 180° conical, cut out 308mm, Ø 354mm x (D)258mm, 6.7Kg	2	C3	390.-
	ACS-40TS	2-way, passive ultra compact ceiling system, LF: 4" / HF: 0.75", 40W AES @16Ohm, 5/10/20@100V, frequency response 106Hz-20kHz +/- 3dB, max. SPL 108dB, 180° conical, cut out 197mm, Ø 221mm x (D)100mm, 2.2Kg	2	<u>C3</u>	165.-
	ACS-55TS	2-way, passive ultra compact ceiling system, LF: 5.25" / HF: 0.75", 50W AES @16Ohm, 7.5/15/30@100V, frequency response 117Hz-20kHz +/- 3dB, max. SPL 113dB, 180° conical, cut out 222mm, Ø 245mm x (D)100mm, 2.8Kg	2	<u>C3</u>	195.-
	ACS-55T	Dito, (D)209mm, 3Kg	2	<u>C3</u>	220.-
	ACP-55TW	Dito, pendant speaker, white		<u>C3</u>	295.-
	ACP-55TB	Dito, pendant speaker, black		<u>C3</u>	295.-

Accessories

	GEB-180T150	Einbetoniergehäuse mit Einbauöffnung 180mm, Höhe Innen 150mm, Höhe Aussen 165mm, Gewicht 1'160 Gr. <u>Passend zu:</u> Martin Audio C4.8T	1	<u>C3</u>	75.-
	GEB-200T150	Einbetoniergehäuse mit Einbauöffnung 200mm, Höhe Innen 150mm, Höhe Aussen 165mm, Gewicht 1'160 Gr. <u>Passend zu:</u> Martin Audio ACS-40TS	1	<u>C3</u>	75.-
	GEB-225T180	Einbetoniergehäuse mit Einbauöffnung 225mm, Höhe Innen 180mm, Höhe Aussen 195mm, Gewicht 1'350 Gr. <u>Passend zu:</u> Martin Audio ACS-55TS, Martin Audio C6.8T	1	<u>C3</u>	75.-
	Adorn CK3	3m cable with carabiner	2	C3	35.- (Stück)

Amplifiers

	iK41 DANTE	4 channel Class D amplifier, 6'000 Watts RMS all channels driven, (1500W per channel @ 2Ω) 96kHz, DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	<u>C3</u>	7'150.-
	iK42 DANTE	4 channel Class D amplifier, 20'000 Watts RMS all channels driven, (5000W per channel @ 2Ω) 96kHz, DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	<u>C3</u>	9'550.-
	iK81 DANTE	8 channel Class D amplifier, 10'000 Watts RMS all channels driven (1250W per channel @ 2/4/8Ω) 96kHz, DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	<u>C3</u>	10'330.-
	VIA2004	Class D, 4x 500W@4Ω, 4x 250W@8Ω, 8Kg	<u>C3</u>	1'295.-
	VIA2502	Class D, 2x 1250W@2Ω, 2x 800W@4Ω, 2x 450W@8Ω, 8Kg	<u>C3</u>	1'950.-
	VIA5002	Class D, 2x 2500W@4Ω, 2x 1600W@8Ω, 10Kg	<u>C3</u>	3'250.-
	VIA5004	Class D, 4x 1250W@2Ω, 4x 800W@4Ω, 4x 450W@8Ω, 10Kg	<u>C3</u>	3'250.-

Controllers

	DX4.0 DANTE	System Controller, 4In / 8Out, AES3, Dante, 1HE	<u>C3</u>	3'895.-
	DX0.4	System Controller, 2In / 4Out, Ethernet, USB, 1HE	<u>C3</u>	715.-
	DX0.6	System Controller, 2In / 6Out, Ethernet, USB, 1HE	<u>C3</u>	975.-

Ersetzt alle bisherigen Preislisten.

Remplace et annule les précédentes listes de prix.

Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.

Articles avec code client gris sont des nouveautés ou ont changé de prix.

Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!