


Der Vertrieb der PanAcoustics Produkte erfolgt durch den autorisierten Fachhandel. Fragen Sie uns an, wir helfen Ihnen sehr gerne weiter.


**Standard colours:** RAL 9006 (aluminium) or RAL-9010 (white) or RAL-9005 (black)

Standard delivery is **without mounting brackets**

## Pan 2-Line

	<b>PB 04-P2L</b>	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 4 x 3.5" wide band chassis, amplifier output power: 4 x up to 40 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), colour: RAL 9006 aluminium	<u>C3</u>
	<b>PB 08-P2L</b>	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 8 x 3.5" wide band chassis, amplifier output power: 8 x up to 40 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), colour: RAL 9006 aluminium	<u>C3</u>
	<b>PB 15-P2L</b>	Compact active digitally controllable column speaker with Beam Steering Technology (single Beam), Drivers: 15 x 2.1" wide band chassis, amplifier output power: 8 x up to 25 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power)	<u>C3</u>
	<b>PB 16-C-P2L</b>	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5" wide band chassis, amplifier output power: 16 x up to 20 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), PB 16-C-PPL consist of tow modules with internal link, colour: RAL 9006 aluminium	<u>C3</u>
	<b>PB 16-C-P2L (one housing)</b>	Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5" wide band chassis, amplifier output power: 16 x up to 20 watt, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), colour: RAL 9006 aluminium	<u>C3</u>
	<b>PB 16-P2L</b>	Compact active digitally steerable line array in column design with Beam Steering Technology, drivers: 16 x 3.5" HQ, amplifier output power: 16 x up to 40 watts, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), PB 16-P2L consists of two modules with internal link	<u>C3</u>
	<b>PB 16-P2L (one housing)</b>	One housing active digitally steerable line array in column design with Beam Steering Technology, drivers: 16 x 3.5" HQ, amplifier output power: 16 x up to 40 watts, Pan 2-Line I/O: 1 x 5-pin connector (audio, control data and power), PB 16-P2L consists of one housing	<u>C3</u>




## Pan Powerline - Control Unit Series




	<b>CCU 2/2-P2L</b>	Central control unit for Pan Powerline system, with two 2-Line outputs (each 200 Watt), each Output has a separate audio input (XLR), preset selector for switching stored presets at connected devices, interface for external media control	<u>C3</u>
	<b>CCU 4/4-P2L</b>	Central control unit for Pan Powerline system, with four 2-Line outputs (each 200 Watt), each Output has a separate audio input (XLR), preset selector for switching stored presets at connected devices, interface for external media control	<u>C3</u>

## Colour option (RAL-XXXX, powder coated, three gloss levels)

	The painting refers to housing and grids in the same colour, different colours (housing, grid) are available on request.			
	CO 04	Colour option RAL-xxxx for Px 04-x	<u>C3</u>	195.-
	CO 08	Colour option RAL-xxxx for Px 08-x & 15-x	<u>C3</u>	365.-
	CO 16	Colour option RAL-xxxx for Px 16-x	<u>C3</u>	550.-
	CO wall mount	Colour option RAL-xxxx for wall mount (without screws)	<u>C3</u>	145.-
	CO stand base	Colour option RAL-xxxx for stand base P/PB	<u>C3</u>	410.-
Default colour for all Pan Beam products is aluminium RAL 9006, or RAL-9010 (white) or RAL-9005 (black), unless another colour information is specified for a product. Usually all products are powdered. colour have to choose by order, with RAL xxxx (4-bit code) and gloss level. Other colour systems are possible, like RAL (3-bit code), NCS, Pantone, DB etc, on request.				

## Mounting accessories

	<b>fixed wall mount</b>	Wall-mount kit for mounting Pan Column-Speaker on wall, vertical 0°/4° in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam, Pan AMT Speakers. (Art. 801840).	<u>C3</u>	90.-
	<b>rotable wall mount (TWM II)</b>	Swivel wall-mount kit for mounting Pan Column-Speaker on wall (bottom and top) in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam, Pan AMT Speakers. (Art. 801840).	<u>C3</u>	135.-
	<b>horizontally rotable wall mount (TWM III)</b>	Wall-mount horizontal turnable kit in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam, Pan AMT Speakers (Art. 801841)	<u>C3</u>	175.-
	<b>stand holder P / PB xx</b>	Stand mount (35mm) in stainless steel. For Pan Speaker, Pan 2-Line, Pan Beam small, Pan AMT small (Art. 801843)	<u>C3</u>	200.-
	<b>wall mount, tiltable, turnable (black)</b>	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, <b>standard colour: black</b> (Art. 801449)	<u>C3</u>	95.-
	<b>wall mount, tiltable, turnable (white)</b>	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, <b>standard colour: white</b> (art. 801450)	<u>C3</u>	95.-
	<b>ceiling mount, fix, (black) PB xx</b>	Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/-45°. Within the parameters - the settings range from 0 to 45°. Max. load is 25kg. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, standard colour: black (art. 801451)	<u>C3</u>	175.-
	<b>Ceiling mount, fix, (white) PB xx</b>	Dito ceiling mount, fix, (black) PB xx but <b>white</b> (art. 801452)	<u>C3</u>	175.-

	<p><b>Telescop ceiling mount, flex, (black) PB xx</b></p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: black (art. 802406)</p>	C3	380.-
	<p><b>Telescop ceiling mount, flex, (white) PB xx</b></p> <p>Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: white (art. 801285)</p>	C3	380.-
	<p><b>Stand base P/PB</b></p> <p>The stand base for P / PB xx (max. two modules), with base plate 450 x 450 [mm] is designed to accommodate Pan Acoustics speaker systems up to a length of 1812 mm of the series Pan Beam, Pan Speaker, Pan AMT. The stand base is in the same design as the speaker. Visually, this forms a common unit and thus results in a successful symbiosis between architecture and sound.</p>	C3	1920.-

*Ersetzt alle bisherigen Preislisten.  
Remplace toutes les listes de prix anciennes.*

*Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.  
Articles avec code client gris sont des nouveautés ou ont changé de prix.*

*Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!  
Articles avec code client souligné demandez leur disponibilité.*